

## APPENDIX C: VISUAL INSPECTION SUMMARY

The results of the visual inspection are in this appendix. This table documents the following information:

- Pile Identification Number;
- Surface Condition;
- Ordered Length;
- Actual Length;
- Sheet Pile Linearity;
- Foot Plate Condition, and
- Sheet Pile Thickness.

**VISUAL INSPECTION SUMMARY**  
**Bay Shore, Long Island, New York**  
**Waterloo Barrier System**

Pile ID #	Surface Condition	Ordered Length (ft.)	Actual Length (ft.)	Linearity	Foot Plate	Pile Thickness (mm)
5	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
6	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
7	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
8	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
9	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
10	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
11	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
12	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
13	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
14	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
15	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
16	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
17	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
18	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
19	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
20	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
21	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
22	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
23	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
24	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
25	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
26	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
27	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
28	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
29	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
30	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
31	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
32	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
33	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
34	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
35	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
36	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
37	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
38	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
39	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
40	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
41	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
42	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
43	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
44	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
45	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
46	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
47	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
48	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5

**VISUAL INSPECTION SUMMARY**  
**Bay Shore, Long Island, New York**  
**Waterloo Barrier System**

Pile ID #	Surface Condition	Ordered Length (ft.)	Actual Length (ft.)	Linearity	Foot Plate	Pile Thickness (mm)
49	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
50	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
51	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
52	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
53	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
54	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
55	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
56	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
57	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
58	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
59	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
60	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
61	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
62	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
63	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
64	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
65	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
66	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
67	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
68	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
69	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
70	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
71	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
72	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
73	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
74	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
75	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
76	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
77	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
78	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
79	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
80	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
81	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
82	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
83	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
84	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
85	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
86	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
87	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
88	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
89	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
90	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
91	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
92	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5

**VISUAL INSPECTION SUMMARY**  
**Bay Shore, Long Island, New York**  
**Waterloo Barrier System**

Pile ID #	Surface Condition	Ordered Length (ft.)	Actual Length (ft.)	Linearity	Foot Plate	Pile Thickness (mm)
93	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
94	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
95	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
96	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
97	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
98	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
99	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
100	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
101	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
102	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
103	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
104	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
105	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
106	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
107	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
108	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
109	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
110	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
111	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
112	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
113	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
114	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
115	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
116	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
117	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
118	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
119	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
120	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
121	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
122	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
123	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
124	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
125	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
126	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
127	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
128	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
129	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
130	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
131	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
132	Acceptable	80.0	80.0	Acceptable	Acceptable	9.5
133	Acceptable	80.0	80.0	Acceptable	Male-Male	9.5
134	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
140	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
141	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5

**VISUAL INSPECTION SUMMARY**  
**Bay Shore, Long Island, New York**  
**Waterloo Barrier System**

Pile ID #	Surface Condition	Ordered Length (ft.)	Actual Length (ft.)	Linearity	Foot Plate	Pile Thickness (mm)
142	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
143	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
144	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
145	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
146	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
147	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
148	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
149	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
150	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
151	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
152	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
153	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
154	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
155	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
156	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
157	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
158	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
159	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
160	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
161	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
162	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
163	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
164	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
165	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
166	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
167	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
168	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
169	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
170	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
171	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
172	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
173	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
174	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
175	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
176	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
177	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
178	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
179	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
180	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
181	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
182	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
183	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
184	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
185	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5

**VISUAL INSPECTION SUMMARY**  
**Bay Shore, Long Island, New York**  
**Waterloo Barrier System**

Pile ID #	Surface Condition	Ordered Length (ft.)	Actual Length (ft.)	Linearity	Foot Plate	Pile Thickness (mm)
186	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
187	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
188	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
189	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
190	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
191	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
192	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
193	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
194	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
195	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
196	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
197	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
198	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
199	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
200	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
201	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
202	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
203	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
204	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
205	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
206	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
207	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
208	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
209	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
210	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
211	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
212	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
213	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
214	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
215	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
216	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
217	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
218	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
219	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
220	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
221	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
222	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
223	Acceptable	75.0	75.0	Acceptable	Male-Male	9.5
224	Acceptable	75.0	75.0	Acceptable	Acceptable	9.5
225	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
226	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
227	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
228	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
229	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5

VISUAL INSPECTION SUMMARY  
 Bay Shore, Long Island, New York  
 Waterloo Barrier System

Pile ID #	Surface Condition	Ordered Length (ft.)	Actual Length (ft.)	Linearity	Foot Plate	Pile Thickness (mm)
230	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
231	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
232	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
233	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
234	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
235	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
236	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
237	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
238	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
239	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
240	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
241	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
242	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
243	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
244	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
245	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
246	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
247	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
248	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
249	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
250	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
251	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
252	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
253	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
254	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
255	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
256	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
257	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
258	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
259	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
260	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
261	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
262	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
263	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
264	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
265	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
266	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
267	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
268	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
269	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
270	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
271	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
272	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
273	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5

VISUAL INSPECTION SUMMARY  
 Bay Shore, Long Island, New York  
 Waterloo Barrier System

Pile ID #	Surface Condition	Ordered Length (ft.)	Actual Length (ft.)	Linearity	Foot Plate	Pile Thickness (mm)
274	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
275	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
276	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
277	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
278	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
279	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
280	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
281	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
282	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
283	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
284	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
285	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
286	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
287	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
288	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
289	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
290	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
291	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
292	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
293	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
294	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
295	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
296	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
297	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
298	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
299	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
300	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5
301	Acceptable	74.0	74.0	Acceptable	Acceptable	9.5